

THE POSSIBILITIES ARE INFINITE



A4 COLOR
DUPLIX
DOCUMENT
SCANNER

fi-5110C


Image Scanner



- A4
- ADF
- Straight Path
- DUPLIX
- COLOR
- IR Multi Feed Detection Sensor
- USB 2.0
- Mono 30 A4 ipm
- Color 30 A4 ipm
- 600 dpi

- WinVista*
- Win XP
- Win Server 2003*
- Win 2000 Professional
- Win Me
- Win98SE
- Win 98

* Windows Vista™ and Windows Server™ 2003 compatible TWAIN drivers are only available as web downloads.



Adobe® Bundled!
Acrobat®
Standard

● Convert any document to a PDF file

for Microsoft® Windows® Operating Systems



● FUJITSU TWAIN Driver



QUALITY SCANNER

As an ENERGYSTAR® partner, PFU Limited, a Fujitsu company, has determined that this product meets the ENERGYSTAR® guidelines for energy efficient. ENERGYSTAR® is a registered trademark in the United States.

fi-5110C Image Scanner

TECHNICAL SPECIFICATIONS

The fi-5110C image scanner with USB 2.0 interface capability expands the market for production scanning. These features will insure Fujitsu's customers' productivity well into the future.

- **Small Footprint**
(W) 293.5 x (D) 166.0 x (H) 130.0mm
- **Fast scanning speed in its class**
 - 15ppm/30ipm A4 portrait at 150dpi (color)
 - 15ppm/30ipm A4 portrait at 200dpi (monochrome)
- **Superior paper handling**
 - 50Sheet ADF Capacity
 - IR multi feed detection
 - Straight paper path and easy maintenance
- **Excellent image quality**
 - Optical resolution of 600dpi
 - Image processing software (Option)
 - Superior CCD (charge-coupled device) image sensing technology
 - Supports sRGB technology
- **Superior input/output performance**
 - USB 2.0 interface
- **Easy to use**
 - Bundled with ScandAll21, Adobe Acrobat 7.0 Standard and other software



*Microsoft, Windows, Windows Server and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries.

*Adobe and Adobe Acrobat are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

*ISIS is registered trademark of EMC Corporation of the United States.

*Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

*Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative. First edition April 2007

Product name		FI-5110C
Scanner type		ADF (Automatic Document Feeder)
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome
Image sensor type		Color CCD (Charge-coupled device) x 2
Light source		White cold cathode discharge lamp
Scanning range		Maximum: A4 (portrait) (210 x 297mm or 8.5 x 11.4in.) Minimum: A8 (portrait) (52 x 74mm or 2.1 x 2.9in.)
Paper weight (Thickness)		52 to 127 g/m ² (14 to 34lb)
Scanning speed (A4 portrait) ^{*1}	Color ^{*2}	Simplex : 15 ppm (150dpi) Duplex : 30 ipm (150dpi)
	Grayscale ^{*2}	Simplex : 15 ppm (200dpi)
	Monochrome	Duplex : 30 ipm (200dpi)
Paper chute capacity ^{*3}		50 sheets (A4: 80 g/m ² or 20 lb)
Background colors		White
Optical resolution		600dpi
Output resolution	Color (24 bit)	50 to 600dpi (adjustable by 1dpi increments)
	Grayscale (8 bit)	
	Monochrome (1 bit)	
Output format		Color: 24bit , Grayscale: 8bit, Monochrome: 1bit
AD converter		1024 levels (10 bit)
Interface		USB 2.0 / USB 1.1
Connector shape		B type
Output mode (half-tone)		Dither / Error diffusion
Voltage or voltage range		AC 100 to 240V, +10% / -10%
Power		Operating: 28W or less (Sleep mode: Less than 6W)
Operational environment		Temperature: 5 to 35°C (42 to 95°F) Relative humidity: 20 to 80% (Non-condensing)
Dimensions: Width x Depth x Height		293.5 x 166 x 130mm (11.6 x 6.5 x 5.1in.)
Weight		2.7kg (5.9lb)
Included drivers		TWAIN, ISIS™
Environmental compatibility ^{*4}		ENERGY STAR® and RoHS
Others	Multi-feed detection	Yes, IR multi-feed detection sensor
	Long paper scanning ^{*5}	863mm (34 in.)
Included items		ADF paper chute, AC cable, AC adapter, USB cable, Setup CD-ROM, Adobe® Acrobat® CD-ROM, Getting Started, QuickScan™ Pro brochure

*1 Actual scanning speeds are affected by data transmission and software processing times.

*2 JPEG compressed figures.

*3 Maximum capacity varies, depending upon paper weight.

*4 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).

*5 The fi-5110C is capable of scanning documents that exceed A4 sheets in length.

Options

Description	Parts number	Comments
Image Processing Software Option V2.5	PA43402-C22901	This image processing software enables the scanner to efficiently binarize scanned data prior to transmission.

Consumables

Description	Parts number	Comments
Pick Roller	PA03360 - 0001	Lifetime : Every 100,000 sheets or one year
Pad ASSY	PA03360 - 0002	Lifetime : Every 50,000 sheets or one year

INFORMATION & IMAGE MANAGEMENT SYSTEMS, S.A.

Valencia, 279, 7ª planta
08009 Barcelona (España)



Tel. (34) 93 272 33 00

Fax (34) 93 487 39 00

<http://www.ims.es>

e-mail: info@ims.es