

fi-6750S

Simplex scanning for the cost conscious user



- 72ppm capable flatbed equipped scanner
- Comes bundled with ScandAll PRO image capture software
- Loaded with "intelligent" functions for more efficient scanning
- Ergonomic ADF

Visit the fi-Series web site for ordering and purchasing information

<http://imagescanner.fujitsu.com/>

A3

Color
72
A4 ppm*

Mono.
72
A4 ppm*

SIMPLEX

*A4 Landscape 200dpi

Features

72ppm Scanning

The fi-6750S' ability to continuously scan up to 200 sheet of different weights, quality and sizes at 72ppm (A4, Landscape, 200dpi) enables it to efficiently digitize large volumes of paper documents. On top of this, the fi-6750S is able to scan paper that is up to 3m long, which enables it to digitize electrocardiograms, instrumental data readings and other long documents.

Comes bundled with ScandAll PRO image capture software

Automatic job separation

The fi-6750S's bundled barcode and patchcode reading functionality enables it to separate different jobs with its automatic job separation function. The result is improved digitizing efficiency.

Seamless Microsoft® Office SharePoint® Server linkability

ScandAll PRO enables the fi-6750S to seamlessly link with Microsoft® Office SharePoint® Server for easy digitized document sharing and viewing administration. The result is even easier document management.

ADF (Virtual Duplex) scanning

fi-6750S bundled ScandAll PRO replicates duplex multi-page scanning by automatically pairing front page images with the appropriate back page images.

Loaded with "intelligent" functions for efficient operation

The fi-6750S is loaded with 2 high end fi-Series functions that enable it to efficiently scan mixed batch documents containing paper of different weights, quality and sizes.

Intelligent multifeed function

The intelligent multifeed function simplifies pre-scanning preparation and improves efficiency by ignoring documents that tend to trigger false multifeed alerts, such as photo and sticky note attached documents.

Trapezoid-shaped and tab attached document cropping / punch hole removal functionality

In addition to being loaded with a function that ensures that trapezoid-shaped documents as well as index tab and sticky note attached documents are scanned in their entirety, the fi-6750S supports a function that removes the circular and angular punch hole representations that are created from scanning loose-leaf sheets, courier service forms and other similar documents.

Ergonomic ADF

- ADF positioning: 2 selectable positions (Center, Left)
- ADF direction: Selectable for left or right handed people when ADF is centrally positioned.



Technical Specifications

Product name		FI-6750S		
Supported operating systems		Microsoft® Windows® 2000 Professional / Microsoft® Windows® XP (32bit/64bit) / Microsoft® Windows Server™ 2003 (32bit/64bit) / Microsoft® Windows Vista™ (32bit/64bit)		
Scanner type		ADF (Automatic Document Feeder) + Flatbed		
Scanning modes		Simplex, Color / Grayscale / Monochrome		
Image sensor type		Color CCD (Charge-coupled device) x 2 (front x 1, Flatbed x 1)		
Light source		White cold cathode discharge lamp x 4 (front x 2, Flatbed x 2)		
Document size	ADF	Maximum: A3 Portrait (297 x 420mm), Double letter (11 x 17in.) Minimum: A8 (52 x 74mm or 2 x 3in.)		
	Flatbed	Maximum: A3 (297 x 420mm), Double letter (11 x 17in.)		
Paper weight (Thickness) *1		A4 / Letter size or smaller: 31 to 209 g/m ² (8.3 to 55.6 lb) Over A4 / Letter size: 52 to 209 g/m ² (13.8 to 55.6 lb) A8 size: 127 to 209 g/m ² (33.8 to 55.6 lb) Card feedability (ADF) *2		
Scanning speed (A4 Landscape) *3	ADF	Color *4	Simplex: 72ppm (200, 300dpi)	
		Grayscale *4		
		Monochrome		
Scanning speed (A4 Portrait) *3	Flatbed	Color / Grayscale / Monochrome	0.6seconds (200dpi) 0.7seconds (300dpi)	
		ADF	Color *4	Simplex: 55ppm (200, 300dpi)
			Grayscale *4	
Scanning speed (A4 Portrait) *3	Flatbed	Color / Grayscale / Monochrome	0.9seconds (200dpi) 1.1seconds (300dpi)	
		Monochrome		
Paper chute capacity (A4 Landscape) *5		200 sheets (A4: 80 g/m ² or 20 lb) (Active loadable ADF)		
Background colors		ADF: White / Black (Selectable) Flatbed: White (Black background is optional.)		
Optical resolution		600dpi		
Output resolution	Color (24bit)	50 to 600dpi (adjustable by 1dpi increments)		
	Grayscale (8bit)			
	Monochrome (1bit)			
Output format		Color: 24bit, 8bit (8 bit and 4 bit with driver) Grayscale: 8bit (4 bit with driver) Monochrome: 1bit		
AD converter		1024 levels (10bit)		
Interface		USB 2.0 / USB 1.1		
Connector shape		B type		
Image processing (half-tone)		Dither / Error diffusion		
Voltage or voltage range		AC 100 to 240V ±10%		
Power consumption		Operating: 216W or less (Sleep mode: less than 6W)		
Operating environment		Temperature: 5 to 35°C (42 to 95°F) Relative humidity: 20 to 80% (Non-condensing)		
Dimensions: Width x Depth x Height *6		690 x 500 x 342mm (27.2 x 19.7 x 13.5in.) Installation space: 1030 x 700 x 640mm (40.6 x 27.6 x 25.2in.)		
Weight		35 kg (77.2 lb)		
Included software / drivers		TWAIN, ISIS™, ScandAll PRO, Adobe® Acrobat®, QuickScan™ Pro (Trial), Image Processing Software Option		
Environmental compatibility *7		ENERGY STAR® and RoHS		
Others	Multi-feed detection	Yes (Standard) ultrasonic multi-feed detection sensor		
	Long paper scanning *8	3048mm (120in.)		
Included items		ADF paper chute, Stacker, AC cable, USB cable, Setup DVD-ROM, Adobe® Acrobat® DVD-ROM, Getting Started, QuickScan™ Pro brochure, Operator panel overlay		

*1 There is no limit of paper weight when document is scanned with the Flatbed.

*2 The fi-6750S supports ISO 7810 card scannability, but cannot scan embossed cards.

*3 Actual scanning speeds are affected by data transmission and software processing times.

*4 JPEG compressed figures.

*5 Maximum capacity varies, depending upon paper weight.

*6 Excluding the ADF paper chute and stacker.

*7 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).

*8 The fi-6750S is capable of scanning the following documents that exceed A3 in length:
- Documents not exceeding 863mm (34in.) in length at resolutions between 201dpi and 400dpi, and documents not exceeding 3048mm (120in.) in length at resolutions between 50dpi and 200dpi with TWAIN and ISIS™. (Long paper scanning does not support resolutions that exceed 400dpi.)

Options

Description	Part number	Comments
Black Document Pad (FI-575BK)	PA03338 - D960	Black flatbed background pads which can be easily replaced by users.

Consumables

Description	Part number	Comments
Pick Roller	PA03338 - K011	Lifetime: Every 250,000 sheets or one year These rollers feed documents into the scanner.
Brake Roller	PA03576 - K010	Lifetime: Every 250,000 sheets or one year These rollers separate documents as they are being fed into the scanner.

Trademarks

Please note that the scanning and printing of paper currency as well as stock and bond certificates is illegal.

- * Microsoft, Windows, Windows Server, Windows Vista and SharePoint are registered trademarks of Microsoft Corporation in the United States and/or other countries.
- * Adobe and Adobe Acrobat are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.
- * ISIS is a registered trademark of EMC Corporation of the United States.
- * Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

⚠ Safety Precautions

- Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
- Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
- Be sure to limit the use of this product to listed power ratings.



As an ENERGY STAR® partner, PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

INFORMATION & IMAGE MANAGEMENT SYSTEMS, S.A.

Valencia, 279, 7ª planta
08009 Barcelona (España)
http://www.ims.es



Tel. (34) 93 272 33 00
Fax (34) 93 487 39 00
e-mail: info@ims.es