

VANDAL-RESISTANT HOUSING PACKAGE



HOUSING DOMO AND PTZ CAMERAS AXIS 213/214/215 AXIS 231/232/233D



GENERAL PRESENTATION

- Patented top-opening system
- Constructed in aluminium with lower semisphere in high quality PMMA
- Indoor/Outdoor installation
- Universal internal adapter for several speed domes and network PTZ cameras
- Camera power supply equipped with internal adapter
- Version with cooling device
- Protection rating IP66 (not for double filter version)
- Wall, ceiling or parapet application with cable management brackets
- Transparent or smoked lower semisphere
- Accessories: fan-assisted heater

TECHNICAL SPECIFICATIONS

General:	Built in aluminium	External dimensions with sunshield:	Diameter: 351 x 335 mm
Lower semisphere:	PMMA transparent or smoked	Without sunshield	Diameter: 314 x 322 mm
Price list code:	HCA2IP66T HCA2IP66A HCA1IP66T HCA1IP66A	Protection standard:	IP 66

INFORMATION & IMAGE MANAGEMENT SYSTEMS, S.A.

Valencia, 279, 7ª planta
08009 Barcelona (España)
<http://www.ims.es>



Tel. (34) 93 272 33 00
Fax (34) 93 487 39 00
e-mail: info@ims.es