

VIDEO SURVEILLANCE CAMERA



BL-C1 CE

Panasonic
ideas for life

OVERVIEW

The **Panasonic BL-C1 CE** IP network camera is ideal to monitor indoors areas. It integrates a 10x digital zoom enabling an accurate view of small details at home or in your business. Thanks to the night view mode, the **Panasonic BL-C1 CE** camera automatically adjusts to any low Light conditions.

Main features:

- 10x digital zoom
- Easy set-up and access to the cameras. It integrates an automatic set-up functionality.(UPnP) that automatically ensures the network connection.
- Colour night view mode: it integrates an automatic adjustment switching on when illumination is not sufficient.
- Motion detection mode; the camera only captures images when a motion is detected in the environment.

TECHNICAL SPECIFICATIONS

Server

Video compression: JPEG (3 levels)
Video resolution: 640x480, 320x240 (by default), 160x120
Frame rate: Max. 7.5 fps. (640x480)
Max. 15 fps. (320x240 or 160x120)
Maximum user access: 20
Supported protocols IPv4: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICPM, POP3, NTP, TCP, UPnP, IPv6, UDP, IP, HTTP, FTP, SMTP, DNS, ICPM, POP3, NDP, NTP, IPsec.
IPsec: Encryption, ESP authentication. M transport (only main mode), IKE tunnel mode.

Camera

Zoom: 10 x zoom digital
Image sensor: 1/4" CMOS sensor, 320,000 pixels.
Illumination: 4-100,000 lx (10 – 100,000 lx when colour night view mode is disabled).
Focus: Fixed 0.3 m to ~
F n°: F 2.8
White balance: Auto/Manual

Angle of view: Horizontal 53°; Vertical 41°
Exposure: Auto

Terminal

Interface: 10Base-T/100Base-TX Ethernet RJ-45 connector x1

System requirements for PC

Operating system: Windows 98SE, 2000, Me, XP
Web server: Internet Explorer 6.0 or later

General

Dimensions 85 mm x 85 mm x 25 mm
Display: Power/
Network communication /
Camera operating /
Ethernet link

Weight: 100 gr.
Power supply Adaptor AC: 9 V DC (120 V AC).
Consumption: 1.7 W c.
Temperature: Operating: +5° a + 40°C
Humidity: 20 %
80% (no condensation)