

## VIDEO-SURVEILLANCE CAMERA



## WV-NP472

**Panasonic**  
ideas for life

### GENERAL PRESENTATION

The new **WV-NP472** network camera allows to capture natural images at entryways, near windows, and in other locations with harsh contrasts between light and dark. It automatically stores images to repose to inputs from motion detectors and external sensor alarms and can send images automatically as e-mail attachments. In addition, the colour camera can also control external devices, turning on lighting or starting a surveillance recorder working. It operates with only 0.8 lx of available light in colour mode and a mere 0.1 lx in black and white. Its Day/Night switching function automatically switches to black-and-white recording when available light is low. This, this single security camera can deliver 24-hour surveillance.

The **WV-NP 472** camera is designed for monitoring over a WAN or over the Internet a snap. Its sophisticated surveillance functions make the **WV-NP 472** the network security camera of choice for a wide range of settings, including banks, office buildings and franchise outlets.

Digital signal processing LSI's for high quality pictures; vertical enhancement for greater picture sharpness; highlight aperture correction for greater picture details of bright objects.

The new **WV-NP 472** directly connects to either digital or analogue devices. Simply set an IP address and connect it to an Ethernet terminal for monitoring and control from a personal computer.

### TECHNICAL SPECIFICATIONS

<b>Pick-up device:</b>	1/3-type interline transfer CCD image sensor.	<b>Interface:</b>	10Base-T/100Base-TX (RJ-45 x 1)
<b>Effective pixels:</b>	753 (H) x 582 (V) pixels	<b>Protocol:</b>	TCP/IP, http, FTP, SMTP, DNS and DHCP.
<b>Min. illumination:</b>	0,1lx (B/W mode), 0,8lx (colour mode at 1,4F)	<b>Video output:</b>	VBS1.0 V (p-p) /75Ω, PAL composite signal.
<b>Synchronisation:</b>	Internal or multiplexed vert. drive	<b>Parallel port:</b>	Alarm input x 1, alarm output x 1, Aux. output x 1, BW/colour select.
<b>Electronic sensitivity up:</b>	Fix: 32x (max.); Auto: 10x (max.)	<b>Power supply:</b>	DC 12V
<b>Alarm activation:</b>	Alarm input, motion detector	<b>Consumption:</b>	700 mA
<b>Alarm notice:</b>	Alarm output / Mail by e-mail	<b>Ambient operating temperature:</b>	-10°C to + 50°C
<b>Alarm log:</b>	Maximum 100	<b>Dimensions (W x H x D):</b>	67 x 65 x 118 mm
<b>Alarm recording:</b>	Multi-shot	<b>Peso:</b>	510g.

INFORMATION & IMAGE MANAGEMENT SYSTEMS, S.A.

Valencia, 279, 7ª planta  
08009 Barcelona (España)  
<http://www.ims.es>



Tel. (34) 93 272 33 00  
Fax (34) 93 487 39 00  
e-mail: [info@ims.es](mailto:info@ims.es)