

▶ Polycom® SoundStation® IP 7000

SIP-Based IP Conference Phone



Astounding voice quality and clarity from the world's most advanced IP conference phone

The SoundStation IP 7000 is a breakthrough conference phone that delivers outstanding performance and a robust feature set for SIP-based VoIP platforms. It is the most advanced conference phone ever developed, and is ideal for executive offices, conference rooms and board rooms.

The SoundStation IP 7000 features Polycom HD Voice technology, boosting productivity and reducing listener fatigue by turning ordinary conference calls into crystal-clear interactive conversations. It delivers high-fidelity audio from 160 Hz to 22 kHz, capturing both the deeper lows and higher frequencies of the human voice for conference calls that sound as natural as being there.

For all conference calls, the SoundStation IP 7000 delivers advanced audio performance that far exceeds previous generations of conference phones. From full-duplex technology that eliminates distracting drop-outs to the latest echo cancellation advancements, only Polycom can deliver a conference phone experience with no compromises.

The SoundStation IP 7000 is the most flexible and expandable conference phone ever developed. Connect two units together for increased loudness and microphone pickup, as well as multiple call control interfaces in the conference room. Connect up to two optional expansion microphones to a single phone to ensure close proximity for everyone in the room. In the future, you will be able to connect the SoundStation IP 7000 to the Polycom HDX high-definition video conferencing system for a complete, integrated voice and video conferencing solution.

In the SoundStation IP 7000, Polycom has combined its rich history in voice conferencing and VoIP technology to develop a groundbreaking new conference phone that is the clear choice for SIP-enabled environments. It shares the same SIP phone software with Polycom's award-winning SoundPoint IP products – the most comprehensive, reliable and feature-rich SIP products in the industry – with proven interoperability with a broad array of IP PBX and hosted platforms.

Plus, the SoundStation IP 7000 features a large multi-line high-resolution LCD display with a full XHTML microbrowser, turning your conference phone into a robust applications platform for your conference room. Bundled applications include advanced three-party conference features and LDAP corporate directory integration.

Make Great Things Happen with the Polycom SoundStation IP 7000 Conference Phone

In today's Internet driven world, the ability to conduct real time communication and collaboration has become critical to an organisation's survival. As the market leader in voice, video and content collaboration and communications, our award-winning conference technology makes it easy for people to interact and maximise productivity over any network, in just about any environment, anywhere around the globe. That's why more organisations worldwide use and prefer Polycom conferencing solutions. Because when people work together, great things happen. See how you too, can achieve great things with the Polycom SoundStation IP 7000 conference phone.

- ▶ HD Voice – Unparalleled clarity to make your conference calls more efficient and productive
- ▶ Polycom's patented Acoustic Clarity Technology – Delivering the best conference phone experience with no compromises
- ▶ Flexible configuration options – Multi-unit connectivity, expansion microphones and future integration with Polycom HDX to meet the needs of many different types of rooms
- ▶ Strong, robust SIP software – Leveraging the most advanced SIP endpoint software in the industry, with advanced call handling, security, and provisioning features
- ▶ Robust interoperability – Compatible with a broad array of SIP call platforms to maximise voice quality and feature availability while simplifying management and administration
- ▶ Large high-resolution display with XHTML microbrowser – Enables new applications that make conference calling easier and more functional

Polycom® SoundStation® IP 7000 Conference Phone Specifications

Additional Features And Benefits

- Equipped with built-in Power over Ethernet (PoE). An optional A/C power kit also available.
- 20-foot microphone pickup, and even more with optional expansion microphones or multi-unit connectivity, reaching all corners of the conference room.
- Automatic Gain Control intelligently adjusts the microphone sensitivity based on where participants are seated in the conference room.
- Features technology that resists interference from mobile phones and other wireless devices, delivering clear communications without distractions.
- Built-in 2.5mm applications port allows you to connect the conference phone to a mobile phone for productive calls even where no network connection is available, or to a computer for calls using PC-based soft phone clients.

Specifications

Power

- IEEE 802.3af Power over Ethernet (built in)
- Optional external universal AC power supply: 100-240V, 1.5A, 48V/50W

Display

- Size (pixels): 255 x 128 (W x H)
- White LED backlight with custom intensity control

Keypad

- Standard 12-key keypad
- Context-dependent soft keys: 4
- On-hook/Off-hook, redial, mute, volume up/down
- Directional navigation wheel

Audio Features

- Loudspeaker
 - Frequency: 160-22,000 Hz
 - Volume: Adjustable to 85 dB at 1/2 meter peak volume
- Full-duplex: Type 1 compliant with IEEE 1329 full duplex standards
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation / DTMF event RTP payload
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Acoustic echo cancellation
- Background noise suppression
- Supported Codecs
 - G.711 (A-law and Mu-law)
 - G.729a (Annex B)
 - G.722, G.722.1
 - G.722.1C
 - Siren 14
 - Siren 22

Call Handling Features

- Shared call / bridged line appearance
- Busy Lamp Field (BLF)
- Distinctive incoming call treatment / call waiting
- Call timer
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way conferencing
- One-touch speed dial, redial
- Call waiting
- Remote missed call notification
- Automatic off-hook call placement
- Do not disturb function

Other Features

- Local feature-rich GUI
- Time and date display
- User-configurable contact directory and call history (missed, placed, and received)
- Customisable call progress tones
- Wave file support for call progress tones
- Unicode UTF-8 character support. Multilingual user interface encompassing Chinese, Danish, Dutch, English (Canada / US / UK), French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish, Swedish

Network and Provisioning

- Ethernet 10/100 Base-T
- 2.5mm connection port
- USB ports: Mini and regular USB 1.1 (not active at launch)
- EX mic ports: Two Walta ports
- IP Address Configuration: DHCP and Static IP
- Time synchronisation with SNTP server
- FTP / TFTP / HTTP / HTTPS server-based central provisioning for mass deployments. Provisioning server redundancy supported.
- Web portal for individual unit configuration
- QoS Support -- IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS and DSCP
- Network Address Translation (NAT) support - static
- RTCP support (RFC 1889)
- Event logging
- Local digit map
- Hardware diagnostics
- Status and statistics
- User selectable ringer tones
- Convenient volume adjustment keys
- Field upgradeable

Security

- Transport Layer Security (TLS)
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server
- HTTPS secure provisioning
- Support for signed software executables

Safety

- UL1950
- CE Mark
- CSA C22.2, No 60950
- EN60950
- IEC60950
- AS/NZSS3260

EMC

- FCC (47 CFR Part 15) Class B
- ICES-003 Class
- EN55022 Class B
- CISPR22 Class B
- AS/NZS 3548 Class B
- VCCI Class B
- EN61000-3-2; EN61000-3-3
- EN55024
- ROHS compliant

Protocol Support

- IETF SIP (RFC 3261 and companion RFCs)

IEEE 802.3af Power over Ethernet version ships with

- Telephone Console
- 25 foot Ethernet cable
- Quick Start Guide
- Quick User Guide
- AC Power version ships with
- Telephone Console
- 25 foot Ethernet cable
- Universal Power Supply
- 7 foot region-specific power cord
- Power Insertion Cable
- Quick Start Guide
- Quick User Guide

Environmental Conditions

- Operating temperature: 0 - 40° C (32 - 104° F)
- Relative humidity: 20%-85% (noncondensing)
- Storage temperature: -30 - 55° C (-22 - 131° F)

Warranty

- 1 year

Country of Origin

- China

Phone Dimensions

- 39.4 x 37.2 x 7.3 cm (15.5 x 14.6 x 2.9 in) (L x W x H)

Phone Console Weight

- 1.08 kg (2.4 lb)

Box Dimensions

- 48.4 x 43.3 x 13 cm (19.1 x 17.0 x 5.1) (L x W x H)

Box Weight

- 2.43 kg (5.4 lb)